PCM-2452WF WiFi 802.11 ac/a/b/g/n 2T2R w/Bluetooth 5.1, M.2/Full-size mPCle, Antennas



Features

- Meets Advantech iDoor technology standard
- M.2 2230 module with mPCle adapter
- IEEE 802.11 ac/a/b/g/n + Bluetooth 5.1
- 2 SMA, 2Tx/ 2Rx ports
- Operating temperature: -40 ~ 85 °C (-40 ~ 185°F)
- Support embedded automation PC UNO series & Panel PC TPC series

Introduction

The PCM-24 series are communication modules from Advantech iDoor Technology. They are all compatible with PCI Express® Mini Card Specification Revision 1.2, including isolated / non-isolated RS-232/422/485 communication cards for automation control, Wi-Fi/3G/GPS/GSM/LTE wireless communication models for data exchange for management and machine level automation applications and PoE function for smart cameras in detection-inspection-production applications. This is a flexible design that enables customers to customize their features with iDoor Technology.

Specifications

General

Bus Type M.2 / mPCle Host Interface WiFi: PCI-E, BT: USB

 Certification CE, FCC

Dimensions M.2 module: 30 x 22 x 2.2mm (1.18" x 0.87"0.09") Module with mPCle adapter: 54.5 x 30 x 5.7mm

(2.15" x 1.18" x 0.22")

I/O Plate: 81 x 19.4 x 41 mm (3.19" x 0.76" x 1.61")

 Power Consumption 3.3V, 389mA (Avg.)

(Wi-Fi continue, BT is off, BW 80MHz) Antenna WiFi 2.4 GHz and 5 GHz dipole antenna WiFi Coaxial Cable, SMA (F) to MHF4, 300 mm Cable

Communications

Security WPA, WPA2

Software

 OS Support Microsoft® Windows® 10/ Linux

Environment

• Operating Temperature $-40 \sim 85$ °C $(-40 \sim 185$ °F)

Regulation

The PCM-24S2WF-CE adopts Intel AC9260 single chip solution and corresponds to its regulations of module Intel AC9260.

Ordering Information

PCM-24S2WF-CE WiFi 802.11 a/b/g/n/ac 2T2R w/BT5, Intel AC9260,

Antenna



