EKI-5729FI-MB

8-Port+2 SFP Entry-Level Managed Switch

Features

- Entry-Level Managed Switch
- Provides wide operating voltage 8.4~52.8 V_{DC}
- C1D2 and ATEX certified for horizontal area
- IXM function enables fast deployment
- Modbus/TCP Enabled by default
- Supports X-Ring for ultra high-speed recovery time less than 20ms

Introduction

Advantech's Entry Level Managed Switches Series are the best deal offer for your Ethernet connections. Advantech's Entry Level Managed Switches Series support the most useful management functions, such as IEEE 802.1Q VLAN, port mirroring, Redundancy, Storm Control, IP Multicast, and provide SNMP v1/v2c, WEB GUI, Standard MIB, Private MIB for access. Advantech's Entry Level Managed Switches Series are also easy and fast deployment from Advantech IXM technology and is compatible with EKI-7700 managed switch series. Advantech's Entry Level Managed Switches Series allow users to expand their industrial network quickly and efficiently, while their rugged industrial-grade design assures reliability and stability.

Specifications

Communications

Standard	IEEE 802.3, 802.3u, 802.3x, 802.1D, 802.1w,802.1p, 802.1Q, 802.1X, 802.3AD,802.3az,802.3ab
LAN	10/100/1000BASE-TX, optional 100BASE-FX, 1000BASE-SX/LX/LHX/XD/ZX/EZX
Transmission Distance	Ethernet: UP to 100 m (4-wire Cat.5e, Cat.6 RJ-45 cable suggested for Gigabit port) SFP: UP to 110 km (depends on SFP)
Transmission Speed	Ethernet: 10/100/1000 Mbps Auto-Negotiation Gigabit Copper: 10/100/1000 Mbps, Auto-Negotiation Gigabit Fiber: UP to 1000 Mbps

Interface

Connectors	8 x RJ45 2 x SFP ports 6-pin removable screw terminal (power & relay)
LED Indicators	P1, P2, P-Fail, Loop detection 10/100/1000T(X): Link/Activity, Speed SFP: Link/Activity

Switch Properties

MAC Table Size	8K
Packet Buffer Size	4.1M bit
Switching Capacity	20 Gbps
Jumbo Frame	9216 bytes

Power

Power Consumption	Max. 6.8 W
Power Input	12 ~ 48 V_{DC} (8.4 ~ 52.8 V_{DC}), redundant dual inputs
Fault Output	1 Relay Output

Mechanism

Dimensions (W x H x D)	43 x 120 x 84 mm
Enclosure	IP30, metal shell with solid mounting kits
Mounting	DIN-Rail, Wall

Protection

Reverse Polarity	Present
Overload Current	Present

Environment

Operating Temperature	-40 ~ 75°C (-40 ~ 167°F)
Storage Temperature	-40 ~ 85°C (-40 ~ 185°F)
Operating Humidity	10 ~ 95% (non-condensing)
Storage Humidity	10 ~ 95% (non-condensing)
MTBF	3,858,286 hours

Certification

EMI	CE, FCC Class A
Safety	UL508
EMC	EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-8
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6
Hazardous Location	Class 1 Division 2, ATEX

L2 Features

VLAN Group	256 (VLAN ID 1 ~ 4094)
VLAN Arrange	Port based VLAN, GVRP
Port Mirroring	Per port, Multi-source port,
IP Multicast	IGMP Snooping v1/v2/v3, MLD Snooping, IGMP Immediate leave
Storm Control	Broadcast, Multicast, Unknown unicast
Redundancy	IEEE 802.1D-STP, IEEE 802.1w-RSTP, XRing Elite, with ultra highspeed recovery time less than 20ms

昊生 研伟科技 15921668847

Dimensions

Unit: mm [inch]



QoS

- **Priority Queue Scheduling** — WRR (Weighted Round Robin), SP (Strict Scheduling Priority) Hybrid Priority
- **Class of Service** — IEEE 802.1p Based CoS, IP TOS, DSCP based CoS
- **Rate Limiting** — Ingress Rate limit, Egress Rate limit
- **Link Aggregation** — IEEE 802.3ad Dynamic Port Trunking, Static Port Trunking

Security

- **Port Security** — Static, Dynamic, MAC address filtering
- **Authentication** — 802.1x (Port-Based, MD5/TLS/TTLS/PEAP Encryption)

Management

- **DHCP** — Client, Option 82
- **Access** — SNMP v1/v2c/v3, WEB, Standard MIB, Private MIB
- **Software upgrade** — TFTP, HTTP, Dual Image
- **NTP** — SNTP client
- **Data** — Syslog
- **Protocols** — Modbus/TCP

Ordering Information

- **EKI-5729FI-MB** — 8-Port+2 SFP Entry-Level Managed Switch Supporting Modbus/TCP w/wide temp